

COUNTY OF TUSCOLA

DEPARTMENT OF BUILDINGS & GROUNDS

MICHAEL MILLER
Director

207 E. Grant
Caro, Michigan 48723
(989) 672-3756
FAX: (989) 672-4011

THOMAS MCLANE
Assistant Director

TO: INTERESTED CONTRACTORS

FROM: MIKE MILLER / DIRECTOR OF BUILDINGS & GROUNDS

DATE: April 21st, 2009

RE: NEW CARPET

Tuscola County will be accepting bids for the installation of new carpet in the District Court Office in the County Courthouse 440 N. State St. Caro, MI 48723. The following specifications shall be considered in your bid:

1. Tuscola County will remove existing furniture.
2. Work is to be done after hours or on weekends.
3. Contractor is to use carpet already selected by the County, please see attached spec. sheets.
4. Carpet shall be direct glued with on pad.
5. Contractor is also to install new vinyl cove base, not yet selected. Please provide samples.
6. Contractor is responsible for cleaning work site after install is complete.

Bids are due by 4:30pm, May 13th, 2009. Bids must be in an envelope marked "Carpet Replacement" on the outside of the envelope. Bids are to be delivered to the Annex building located at 207 E. Grant st., Caro, MI 48723.

All work is to be done by qualified personal.

Contractors shall provide proof of liability insurance.

Any questions please call Mike Miller at 989-672-3756.

Tuscola County reserves the right to reject any and all bids, and to except the bid that is in the best interest of the County. Any vender or parties who bids under this policy are doing so of their own free will and without liability to the County. A bid may be awarded to a higher bidder for reasons such as, but not limited to: quality, service, reliability, convenience, dependability, etc.

Color - Augustine

SOCRATES N 2B - 10069

PRODUCT SPECIFICATIONS

Type Yarn:	100% EcoSolution Q® Premium Branded SD Nylon with Lifetime Stain Warranty containing post industrial and/or post consumer recycled content
Construction:	Textured Loop
Dye Method:	Solution Dyed
Ply:	3 - 5
Gauge:	1/8
Stitches Per Inch:	7.5
Tufted Pile Height:	5/32" (.156") - 7/32" (.218")
Yarn Weight: (sq. yd.)	28 oz.
Finished Pile Thickness:	.170
Density:	5929
Weight Density:	186,024
Special Treatments:	Patcraft SP™
Primary Backing:	Woven Polypropylene
Secondary Backing:	Everbond® EX
Width:	12'

PERFORMANCE SPECIFICATIONS

Flammability:	Passes
Nathanamias PBI Test (DOC FF-1-70):	Class I
Flooring Radiant Panel (ASTM E-649):	Less Than 450
Smoke Density (ASTM E-662):	Lifetime Commercial Wear Warranty
Wearability:	Lifetime Colorfastness to Light
Colorfastness Warranties:	Lifetime Colorfastness to Atmospheric Contaminants
Edge Ravel, Zippering & Delamination:	Lifetime Warranties
Stain Removal:	Lifetime Stain Removal Limited Guarantee
Traffic Class:	Extra Heavy
CRI Green Label:	23252271
ADA Compliance:	This Product Meets the Guidelines as Set Forth in the Americans with Disabilities Act for Minimum Static Coefficient of Friction of 0.6 for Accessible Routes.

***SPECIFICATIONS ARE SUBJECT TO NORMAL MANUFACTURING TOLERANCES**

NO PATTERN REPEAT